



Holzvergaser HERLT Serie	HV	15	22	35	40	45-B	49	65	66	100	145	
Nennwärmeleistung	kW	15	22	35	40	45	49	65	66	100	145	
Leistungsbereich	kW	13-18	14-25	22-40	35-45	40-57	40-49	50-72	55-75	80-115	120-180	
zulässiger Betriebsüberdruck	bar	3	3	3	3	3	3	3	3	3	3	
Kesselgewicht ohne Wasser	kg	780	580	740	920	1280	1332	1350	1550	1575	2300	
maximale Scheitholzlänge	cm	55	55	55	75	75	105	105	105	105	120	
Füllraumvolumen	l	300	150	250	370	370	500	500	720	720	1200	
empfohlene Pufferspeichergröße	l		2500	4000	5000	6000	6000	7500	9000	10000	15000	
Gesamthöhe	A	mm	1800	1500	1670	1670	1770	1860	1860	2240	2240	2500
Gesamtbreite	B	mm	1070	812	955	955	1080	1040	1040	1100	1100	1460
Gesamttiefe	C	mm	1600	1700	1700	1920	2700	2550	2550	2550	2550	2700
Höhe Gebläsestutzen	D	mm	1300	1100	1400	1400	-	1500	1500	1930	1930	2100
Höhe Gebläsestutzen	E	mm	1600	1500	1600	1600	-	1700	1700	2130	2130	2500
Innenmaß Abgasstutzen		mm	169	169	169	169	169	238	238	238	238	286
min. Breite Transportweg		mm	890	680	824	824	824	824	824	864	864	1260
Rohranschlüsse			1"	1"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	2"	2"

